

Issue Date: 01-Sep-2012

Revision Date: 01-Aug-2017

Version 4

1. IDENTIFICATION

Product Identifier

Product Name Slide Quick RP Rust Preventive

Other means of identification

SDS # 42810R

Product Code 42810R

Synonyms Rust Preventive Compound

Quick RP

UN/ID No UN1950

Other Information Formula: 54891.

Recommended use of the chemical and restrictions on use

Recommended Use Industrial rust preventive.

Details of the supplier of the safety data sheet

Supplier Address

BMS France

53, route des Contamines - 74370 Argonay

France

Emergency Telephone Number

Company Phone Number

Phone: +33 (0)4 50 27 29 00

Mail: info@bmsfrance.eu

Emergency Telephone (24 hr)

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Red tint liquid

Physical State Aerosol

Odor Faintly disagreeable odor

Classification

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard Statements

Causes skin irritation
 Suspected of damaging fertility or the unborn child
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol

**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms Rust Preventative Compound
 "Dry" Rust Preventative.
Chemical Family Petroleum derivative.

Chemical Name	CAS No	Weight-%
Hexane	110-54-3	55-65
Propane	68476-86-8	25-35
Benzenesulfonic Acid, mono-C16-24-alkyl Derivatives	70024-71-4	5-10

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	When symptoms persist or in all cases of doubt seek medical advice.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash with soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician if you feel unwell.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	Aspiration hazard: if swallowed can enter lungs and cause damage. Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion or loss of coordination. May cause irritation to the mucous membranes and upper respiratory tract.
-----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂). Foam. Water.

Unsuitable Extinguishing Media Use water spray with caution to prevent the spread of flames.

Specific Hazards Arising from the Chemical

Extremely flammable. Pressurized container: May burst if heated. Containers may explode when heated. Vapors are heavier than air and may spread along floors. Combustion products may be toxic.

Hazardous Combustion Products Carbon oxides. Oxides of sulfur. Various unidentified organic compounds.

Sensitivity to Mechanical Impact Yes.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Move containers from fire area if you can do it without risk. Cool containers exposed to fire with water. Do not release runoff from fire control methods to sewers or waterways.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Ventilate affected area. Remove all sources of ignition. Refer to protective measures listed in sections 7 and 8.
Environmental Precautions	Do not allow material to contaminate ground water system. Prevent product from entering drains. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment	Remove leaking container to outside disposal site.
Methods for Clean-Up	Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Do not spray on an open flame or other ignition source. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Avoid contact with skin, eyes or clothing. Always replace cap after use. Empty containers may contain flammable vapors/residue.
--------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat. Inspect containers periodically for defects. Protect container from physical damage. Protect from sunlight.
Incompatible Materials	Oxidizing agents. Halogenated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

Appropriate engineering controls

Engineering Controls	Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn. Eyewash stations. Showers.
-----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear eye/face protection. Goggles.
Skin and Body Protection	Wear suitable gloves. Wear suitable protective clothing.
Respiratory Protection	Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure limits are exceeded.

General Hygiene Considerations	Do not breathe vapors or spray mist. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.
---------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Odor	Faintly disagreeable odor
Appearance	Tan liquid	Odor Threshold	Not determined
Color	Tan		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting Point/Freezing Point	< -40 °C / <-40 °F	
Boiling Point/Boiling Range	39.4-40 °C / 103-104 °F	
Flash Point	No information available	
Evaporation Rate	No information available	
Flammability (Solid, Gas)	Flammable aerosol	
Upper Flammability Limits	7.5%	
Lower Flammability Limit	1.2%	
Vapor Pressure	137 mmHg	@ 21 °C (70 °F)
Vapor Density	Heavier than air	
Specific Gravity	0.644	
Water Solubility	None	
Solubility in other solvents	No information available	
Partition Coefficient	No information available	
Auto-ignition Temperature	No information available	
Decomposition Temperature	No information available	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	No information available	
Explosive Properties	Pressurized container: May burst if heated	
Oxidizing Properties	None known	
VOC Content (%)	No information available	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid direct sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Do not puncture or incinerate cans.

Incompatible Materials

Oxidizing agents. Halogenated compounds.

Hazardous Decomposition Products

Carbon oxides. Sulfur oxides. Various unidentified organic compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	Causes skin irritation.
Inhalation	Do not inhale.
Ingestion	Do not ingest.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hexane 110-54-3		2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through		1000: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Propane 68476-86-8	<=2.8

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Hexane 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Based on package size, product may be eligible for limited quantity exception.

DOT (each not exceeding 1 L capacity)

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

IATA

UN/ID No UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1

IMDG

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION**International Inventories**

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Hexane	Present	X		Present		Present	X	Present	X	X
Propane	Present	X		Present			X	Present	X	X
Benzenesulfonic Acid, mono-C16-24-alkyl Derivatives	Present	X				Present	X	Present	X	X

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances**AICS - Australian Inventory of Chemical Substances***US Federal Regulations****CERCLA**

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexane 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	60	1.0

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane 110-54-3	X	X	X

16. OTHER INFORMATION

NFPA**Health Hazards****Flammability****Instability****Special Hazards**

Not determined

Not determined

Not determined

Not determined

HMIS**Health Hazards****Flammability****Physical Hazards****Personal Protection**

1

4

0

B

Issue Date: 01-Sep-2012
Revision Date: 01-Aug-2017
Revision Note: New color description

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet