Regulation EC No 1907/2006 Art.31

**Productname:** FORMULA 2

**Ref.Nr.:** UDS000270\_3\_20170629 (EN)

Creationdate : Replaces:

29.06.17 Version: 1.1 UDS000270 20150108

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

#### **FORMULA 2**

Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Release Agents

#### 1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Ambersil House - Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Tel.: +44 1278 727200 Fax.: +44 1278 425644 E-mail: hse.uk@crcind.com

### 1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Classification is based on test data.

**Health:** Skin irritation, category 2 Causes skin irritation.

Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Classification based on calculation method.

**Environment:** Hazardous to the aquatic environment, chronic category 3

Harmful to aquatic life with long lasting effects.

Classification based on calculation method.



### Regulation EC No 1907/2006 Art.31

 Productname :
 FORMULA 2
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000270\_3\_20170629 (EN)
 Replaces:
 UDS000270\_20150108

#### 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

**Product identifier:** Contains:

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Hazard pictogram(s):

<u>(</u>

Signal word: Danger

**Hazard statement(s):** H222 : Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

**Precautionary statement(s):** P102 : Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261 : Avoid breathing dust/fume/gas/mist/vapours/spray. P271 : Use only outdoors or in a well-ventilated area.

P410/412: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F.

P501-2: Dispose of contents/container to an authorised waste collection point.

### 2.3. Other hazards

No information available

# SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

#### 3.2. Mixtures

distillate Petroleumgas (1,3-butadiene < 2119485926- 20 91-4 990-9 60 Gas 1 H280,H220 K,G Gas 1 H280,H220 K,G 91-4 990-9 60 Gas 1 H280,H220 K,G Ga	Hazardous ingredient	Registration number	CAS- nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics  2119456620- 43  - (926- 141-6) 30  Asp. Tox. 1  H304  B,Q  Plam. Liq. 2, Skin Irrit. 2119484651- 2119484651- 30  Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic	Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	2119485926-				· · · · · · · · · · · · · · · · · · ·	H280,H220	K,G
hydrocarbons,C6,isoalkanes,< 5% n-hexane	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	2119456620-	-			Asp. Tox. 1	H304	B,Q
	hydrocarbons,C6,isoalkanes,< 5% n- hexane	2119484651-	-	V		2, STOT SE 3, Asp. Tox. 1, Aquatic		Q



### Regulation EC No 1907/2006 Art.31

 Productname :
 FORMULA 2
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000270\_3\_20170629 (EN)
 Replaces:
 UDS000270\_20150108

B: substance with national established workplace exposure limit

G: exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

K: not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

Q: The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

(\* Explanation phrases : see chapter 16)

# SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Contact with eyes: If substance has got into eyes, immediately wash out with plenty of water

If eye irritation persists: Get medical advice/attention.

**Contact with skin:** Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

**Inhalation:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

**Ingestion:** If swallowed do not induce vomiting because of risk of aspiration into the

lungs. If aspiration is suspected obtain immediate medical attention

#### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation :** Excessive inhalation of solvent vapours may give rise to nausea, headaches

and dizziness

**Ingestion:** After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

Symptoms: sore throat, abdominal pain, nausea, vomiting

**Skin contact :** Irritating to skin

Symptoms: redness and pain

**Eye contact :** May cause irritation.

Symptoms: redness and pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice:** If you feel unwell, seek medical advice (show the label where possible

If symptoms persist always call a doctor

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

foam, carbon dioxide or dry agent

### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO,CO2



Regulation EC No 1907/2006 Art.31

FORMULA 2 Creationdate: Productname:

29.06.17 Version: 1.1 Ref.Nr.: UDS000270 3 20170629 (EN) Replaces: UDS000270 20150108

### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water In case of fire, do not breathe fumes

#### SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing and gloves.

### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

### 6.4. Reference to other sections

For further information see section 8

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Equipment should be earthed

Use explosion-proof electrical/ventilating/lighting/.../equipment.

Use only non-sparking tools.

Do not breathe aerosols or vapours.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection/face protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

## 7.3. Specific end use(s)

Release Agents



Regulation EC No 1907/2006 Art.31

FORMULA 2 Productname:

Creationdate: 29.06.17 Version: 1.1 Ref.Nr.: UDS000270 3 20170629 (EN) Replaces: UDS000270 20150108

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### **Exposure limits:**

No information available

#### 8.2. Exposure controls

Control procedures: Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection: Take precautions to avoid contact with skin and eyes when handling the

product.

In all cases handle and use the product in accordance with good industrial

hygiene practices.

Ensure adequate ventilation

inhalation: In case of insufficient ventilation, wear suitable respiratory equipment.

hands and skin: When handling the product wear chemical-resistant gloves (standard EN 374).

Use a reusable glove with a minimum breakthrough time of 30 minutes. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be

changed part-way through.

Recommended gloves: Nitrile

Wear safety eyewear according to EN 166.

**Environmental protection:** Avoid release to the environment.

Collect spillage.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Liquid under pressure. Apperance : physical state : colour: Colorless.

odour: Solvent. Not applicable. pH:

Boiling point/range: 55 °C Flash point: - 26 °C Evaporation rate: Not available.

Explosion limits: upper limit: 9.4 % lower limit: 1.1 %

Vapour pressure: Not available.

Relative density: 0.75 g/cm3 (@ 20°C). Solubility in water : Insoluble in water

Auto-ignition: > 200 °C Viscosity: Not available.



Regulation EC No 1907/2006 Art.31

Productname: FORMULA 2

**Ref.Nr.:** UDS000270\_3\_20170629 (EN)

**Creationdate :** 29.06.17 Version : 1.1 **Replaces:** UDS000270\_20150108

### 9.2. Other information

VOC = volatile organic compounds

602 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

## 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

### 10.4. Conditions to avoid

Avoid overheating

### 10.5. Incompatible materials

Strong oxidising agent

## 10.6. Hazardous decomposition products

CO,CO2

## SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

acute toxicity:	based on available data the classification criteria are not met
skin corrosion/irritation:	Causes skin irritation.
serious eye damage/irritation:	based on available data the classification criteria are not met
respiratory or skin sensitisation:	based on available data the classification criteria are not met
germ cell mutagenicity:	based on available data the classification criteria are not met
carcinogenicity:	based on available data the classification criteria are not met
toxicity for reproduction:	based on available data the classification criteria are not met
STOT-single exposure:	May cause drowsiness or dizziness.
STOT repeated exposure:	based on available data the classification criteria are not met
aspiration hazard:	based on available data the classification criteria are not met



### Regulation EC No 1907/2006 Art.31

**Productname:** FORMULA 2

**Ref.Nr.:** UDS000270\_3\_20170629 (EN)

Creationdate : Replaces:

29.06.17 Version: 1.1 UDS000270 20150108

### Information on likely routes of exposure:

Inhalation: Inhalation of solvent vapours may give rise to nausea, headaches and

dizziness

**Ingestion:** After vomiting of swallowed product aspiration into lungs is likely. Solvents

may induce chemical pneumonia.

**Skin contact :** Irritating to skin **Eye contact :** May cause irritation.

### Toxicological data:

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	>5000 mg/kg
		LD50 derm.rabit	> 5000 mg/kg
hydrocarbons,C6,isoalkanes,< 5% n-hexane	-	LD50 oral rat	> 5000 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 3000 mg/kg

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Hazardous to the aquatic environment, chronic category 3 Harmful to aquatic life with long lasting effects.

### **Ecotoxicological data:**

Hazardous ingredient	CAS-nr.	method	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	IC50 algae	1000 mg/l
		LC50 fish	1000 mg/l
		EC50 daphnia	1000 mg/l
hydrocarbons,C6,isoalkanes,< 5% n-hexane	-	IC50 algae	55 mg/l
		LC50 fish	> 1 mg/l
		EC50 daphnia	3.87 mg/l

### 12.2. Persistence and degradability

No information available

## 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

Insoluble in water



Regulation EC No 1907/2006 Art.31

Productname: FORMULA 2

**Ref.Nr.:** UDS000270\_3\_20170629 (EN)

Creationdate : Replaces:

29.06.17 Version : 1.1 UDS000270 20150108

#### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No information available

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**Product:** This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised

waste collection point.

**Contaminated packaging:** Disposal should be in accordance with local, state or national legislation

# **SECTION 14: Transport information**

### 14.1. UN number

UN-number: 1950

### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Class: 2.1 ADR/RID - Classification code: 5F

### 14.4. Packing group

Packing group: Not applicable.

### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous:

IMDG - Marine pollutant:

IATA/ICAO - Environmentally hazardous:

## 14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)



### Regulation EC No 1907/2006 Art.31

 Productname :
 FORMULA 2
 Creationdate :
 29.06.17 Version : 1.1

 Ref.Nr.:
 UDS000270\_3\_20170629 (EN)
 Replaces:
 UDS000270\_20150108

 IMDG - Ems:
 F-D, S-U

 IATA/ICAO - PAX:
 203

 IATA/ICAO - CAO
 203

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

### 15.2. Chemical safety assessment

No information available

## SECTION 16: Other information

\*Explanation hazard statements: H220 : Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

acronyms and synonyms: TWA = time weight average

STEL = short time exposure limit VOC = volatile organic compounds PBT = persistant bioaccumulative toxic vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

