



## Balgensauger mit 1,5 Falten Bellows Vacuum Cup with 1,5 folds

- > Härte / Hardness: 55° ± 5 Shore A
- > Einsatzbereich / Application area: -40°C - 160°C

### Technische Daten / Technical Specifications

Artikel-Nummer Item number	Gewicht [g] Weight [g]	passende Halter suitable Fastener
23.011.008.14/2	1	270.013 (M5-AG) 270.103 (M6-AG) 270.003 (G1/8-AG) 270.015 (G1/8-IG)
23.016.016.14/2	2	270.013 (M5-AG) 270.103 (M6-AG) 270.003 (G1/8-AG) 270.015 (G1/8-IG)
23.020.124.14	3	270.311 (M5-AG) 270.063 (G1/8-AG) 270.061 (G1/8-IG)
23.030.125.14	8	270.030 (G1/8-AG) 270.019 (G1/8-IG) 270.274 (G1/4-AG) 270.275 (G1/4-IG)

- > gute Hitze-, Öl-, und Chemikalienbeständigkeit
- > abdruckarm
- > LABS- und silikonfrei
- > gute Ozon-Witterungsbeständigkeit
- > Good resistance to heat, oil and chemicals
- > Low marking
- > Free of silicone and other varnishing disturbing substances
- > High resistance to ozone and elements

### Abmessungen / Dimensions

<p>23.011.008.14/2</p>	<p>23.016.016.016/2</p>	<p>23.020.124.14 23.030.125.14</p>					
Artikel-Nummer Item number	ø D [mm]	ø d1 [mm]	ø d2 [mm]	d3 [mm]	d4 [mm]	H [mm]	Hub [mm] Lift [mm]
23.011.008.14/2	12	10	5	12	4,5	16	4,5
23.016.016.14/2	16	10	5	17	8	19	6
23.020.124.14	22	15	4,5	24	10	20	8
23.030.125.14	32	20	6	36	17	30	9