



Balgensauger mit 2,5 Falten Bellows Vacuum Cup with 2,5 folds

- > Härte / Hardness: 55° ± 5 Shore A
- > Einsatzbereich / Application area: -40°C - 160°C

Technische Daten / Technical Specifications

Artikel-Nummer Item number	Gewicht [g] Weight [g]	passender Halter Suitable Fastener
21.011.095.14	< 1	270.134 (M5-AG) 270.104 (M6-AG) 270.003 (G1/8-AG) 270.015 (G1/8-IG)
21.014.053.14	1	270.134 (M5-AG) 270.104 (M6-AG) 270.003 (G1/8-AG) 270.015 (G1/8-IG)
21.020.016.14/2	2	270.013 (M5-AG) 270.103 (M6-AG) 270.003 (G1/8-AG) 270.015 (G1/8-IG)
21.032.075.14/3	10	270.132 (G1/8-AG) 270.114 (G1/8-IG) 270.190 (G1/4-AG) 270.192 (G1/4-IG)
21.043.049.14	18	270.132 (G1/8-AG) 270.114 (G1/8-IG) 270.190 (G1/4-AG) 270.192 (G1/4-IG)
21.060.051.14	43	270.281 (G1/4-AG) 270.282 (G1/4-IG)

- | | |
|--|---|
| <ul style="list-style-type: none"> > gute Hitze-, Öl-, und Chemikalienbeständigkeit > abdruckarm > LABS- und silikonfrei > gute Ozon-Witterungsbeständigkeit | <ul style="list-style-type: none"> > Good resistance to heat, oil and chemicals > Low marking > Free of silicone and other varnishing disturbing substances > High resistance to ozone and elements |
|--|---|

Abmessungen / Dimensions

<p>21.011.095.14</p>	<p>21.014.053.14</p>	<p>21.020.016.14/2 21.032.075.14/3 21.043.049.14 21.060.051.14</p>
----------------------	----------------------	--

Artikel-Nummer Item number	ø D [mm]	ø d1 [mm]	ø d2 [mm]	d3 [mm]	d4 [mm]	H [mm]	Hub [mm] Lift [mm]
21.011.095.14	10,5	8	4	8	5	15	5
21.014.053.14	14	8	4	15	5,5	18	9
21.020.016.14/2	20	10	4,5	20	10	23	9
21.032.075.14/3	32	18	8	32	17	36	13
21.043.049.14	42	20	8	42	16	45	19
21.060.051.14	60	22	8	60	28	55	25